

SVR-2016NE



Product Summary

- 1080P (1920x1080P) 480fps Recording.
- 1080P, 720P, 960H selectable.
- Various video output port (HDMI, VGA, BNC)
- Various video output mode (Full HD,XGA, SDTV)
- RAID 1/5/10 Option.
- Internal HDD 3ea, 1 eSATA
- ONVIF
- Video clip (Backup viewer),
JPEG Still Image, Log list, Setup data
- Covert channel, Private Zone
- Apple Mac OS
- iPhone, Android, iPad
- 8 PoE

Major Specifications

Model Name		SVR-2016NE
System	OS	Embedded Linux
	Language	Chinese, Chinese(S), Dutch, English, French, German, Hebrew, Hungari, Italian, Japanese, Korean, Latvian, Persian, Polish, Portuguese, Russian, Spanish, Sweden, Turkish
	Time Accuracy	5ppm (12.5sec/month)
	Time Sync.	NTP, GMT, DST
	User	15 Users (Admin., User1 ~ User14)
	Access	Front button, Mouse, Remocon, Network, Key controller
	Hexaplex Upgrade	Live monitoring, Recording, Playback, Backup, Network, Setup
Camera	IP Camera	USB2.0 Memory stick, Network
Video	System	ONVIF
	Input	NTSC / PAL - Config switch
	Display Rate	16ch
	Output Interface	Max. 1080p 480/400fps
	Output Resolution	HDMI, VGA, BNC
Audio	Spot	Full HD
	Input Interface	N/A
	Output Interface	16 IPC
Video Recording	Compression	HDMI
	Speed	H.264
	Resolution	Max. 480/400fps
	Mode	Max.2MP/ch
	Event	Schedule
Audio Recording	Bit Rate	Motion, Local Sensor
	Compression	64Mbps
	Audio Sampling Rate	G.711
Playback	Audio Bit Rate	Depends on IPC
	Search	Depends on IPC
	Mode	Go to first rec. time, Go to last rec. time, Go to last search time, Calenda, Log viewer, Smart search, Multi-time & day search, Event search
Network	Interface	Event only playback, Backward, Pause, Frame by frame, Speed up (x1 ~ x32, x300)
	Compression	RJ45 (Ethernet 10/100/1G) x 1
	Speed	H.264
Backup	Resolution	Max. D1 30fps in total
	Interface	Max. 1080p
	Format	USB2.0, DVD, Network
Bootling	Live	Video clip (Backup viewer), JPEG Still Image, Log list, Setup data
	Recording	40sec
	Post-Alarm	50sec
Alarm	Motion Grid	5sec~5min
	Alarm Action	14x15 (NTSC/PAL)
	Input / Output	E-mail, Event Popup, Buzzer, Relay, PTZ Preset, Remote CMS, Front LED
	HDMI	4/1 - EOL
Display	VGA	Full HD
	TV	Full HD
	Mode	SDTV(720x480/576)
	Camera Title Name	16/9/4/1/SEQ/BIG - LIVE, 16/9/4/1 - P.B
External Interface	PTZ / Keyboard	English : 20 characters Chinese, Japanese, Korean : 10 characters
	ATM/POS	2 RS485 - Terminal Block
Storage	Primary	RS232C - Terminal Block, Ethernet POS
	External	3 HDD
	ODD	1 eSATA
Features	POE	1 DVD
	Jog-shuttle	8PoE
	HW RAID	N/A
	EOL	RAID1/5/10 Options
	Digital Zoom	Yes
	Watermarking	x1 ~ x16
	Two-way Audio	Yes
	Detection / Search	N/A
	Fan Fail	Motion, Sensor
	E-mail	Yes
	Capture	5 User
	iSCS Recording	1080p
	DDNS, DHCP, UPNP	Yes
	CMS, VMS, RMS	Yes
	Smart Phone (3G)	Windows
	Mac Viewer	Android, iPhone, iPad
	Input Voltage (DVR)	Apple Mac OS
	Input Voltage (PoE)	DC 12V, 5A
Electrical	Camera Power Output	54xx series : DC48V / 1A, 58xx series : DC48V / 2A
	Power Supply	51xx : N/A, 54xx : Max. 30 W per channel, Up to Total 40W, 58xx : Max. 30 W per channel, Up to Total 80W
	Operating Temp.	12V/5A - Level 5
General	Humidity	5 ~ 40 °C
	Weight w/o HDD	10 ~ 80%
	Dimension	4Kg
	Certification	430 x 86 x 270 mm
		CE, FCC, RoHS Compliance