


SDP22T-VIR8024N



Dimensions



Product Summary

- 1/2.9" SONY CMOS 2.48M Sensor
- Full HD (1920 x 1080P 30fps) A-HD Output
- DWDR (Digital Wide Dynamic Range)
- 3D + 2DNR (Digital Noise Reduction)
- SENS UP, SMART IR, DEFOG
- HLMASK (High Light Masking)
- Privacy Masking, Motion Detection
- LSC (Lens Shading Correction)
- ACE (Adaptive Contrast Enhancer)
- 2.8~12mm Mega Pixel Lens
- OSD (On Screen Display-Option)
- CVBS Out (For Installer-Option)

Major Specifications * OSD Menu is subject to change without prior notice / *AHD output can be changed by TVI, CVI or CVBS

| MODEL NAME | SDP22T-VIR8024N | |
|-----------------------|---|----------------|
| Image Device | 1/2.9" SONY CMOS, 2.43Megapixel | |
| Total Pixels | 2,000(H) x 1,241(V) / 2,482,000 (Pixel) | |
| Effective Pixels | 1,984(H) x 1,225(V) / 2,430,400 (Pixel) | |
| Scanning System | 2:1 Interlace | Non- Interlace |
| Synchronization | Internal Synchronization | |
| Horizontal Resolution | 1080P @30fps | 1080P @25fps |
| Video Output | AHD,TVI,CVI or CVBS OUTPUT | |
| S/N Ratio | More Than 52dB (AGC OFF / F1.2) | |
| Shutter / AGC | Auto (High, Low Luminance) / Manual | |
| White Balance | ATW (Speed, Delay, ATW, Environment) / User1,2 / Manual | |
| Picture Adjustment | Mirror / Brightness / Contrast / Sharpness / Hue / Gain | |
| ATR | ON / OFF | |
| Motion / Privacy | ON / OFF | |
| Lens | 2.8~12mm Mega Pixel Lens | |
| LED | 24LED | |
| Storage Temp. | 14°F ~ 122°F (-10°C ~ + 50°C) | |
| Operating Temp. | 4°F ~ 140°F (-20°C ~ + 60°C) | |
| Humidity | Less than 80% | |
| Cable | Standard 1.0m BNC/DC Jack | |
| Power Source | DC12V 300mA | |
| Dimensions | 81.4mm(Φ) X 89.8mm(H) | |
| Net Weight | Approx. 720g | |