


SV-555G30P



Dimensions



Product Summary

- 1/2.8" Sony STARVIS CMOS sensor
- FHD resolution 1920 x 1080P real-time
- Low illumination 0.001Lux
- Day/Night (ICR), AWB, 2D/3D-DNR, IR-CUT
- D-WDR, Motion Detection, Privacy Mask, Mirror, rotate
- RTSP and Onvif 2.6 compatible
- H.265/H.264 dual-stream media server
- Easy-to-use P2P Cloud service
- Multi web browser, PC Client, mobile APP remote access
- Optional customization Lens/Audio/POE, etc.
- Lightning protection 4000V
- Strong water-proof housing, IP65
- 6 pcs SMD Array IR Leds, IR distance 30-40 meters
- Network PTZ control , 4 times optical zoom
- HD 2.8- 12 mm Auto Focus Motorized lens

Major Specifications

* Specifications are subject to change without prior notice.

Model Name		SV-555G30P
Camera	Image Sensor	1/2.8" 5MP IMX335 CMOS
	Effective Pixels	3096(H)×2196 (V)
	Electronic Shutter	AUTO, 1/25s ~ 1/100000s
	Min. Illumination	0.01Lux@F1.2(AGC ON), 0Lux IR on
	Day/Night	Auto/Color/(B/W)/Timing
	WDR	Digital WDR
	White Balance	Auto/Manual
	AGC/BLC	Support
	DNR	2D/3D DNR
Other	Multi-lines OSD, Motion Detection, Privacy Mask, Mirror, Rotate	
Encode	Embedded Solution	MC316DM
	Video Standard	H.265/H.264
	Video Resolution	Main Stream:15ps@5MP(2592x1944),25fps@4MP(2592x1520),30fps@3MP/1080P/720P Sub stream: VGA/360P@30fps, etc.
	Video Bitrates	32Kbps - 8Mbps, VBR/CBR
	Audio Standard	G.711-u/G.711-a
	OSD Overlay	Title and Time overlay
IR Led	IR Led	6 pcs SMD array IR Led
	IR Distance	30-40 M
Lens	Focal length	2.8-12 mm AF lens
	Zoom	4x optical zoom
Optional Function		POE, Audio, etc.
PTZ	Pan/Tilt Range	Pan: 0° ~ 180°; Tilt: 0° ~ 55°
	Preset Point	1
	Manual Control Speed	Pan: 0.5° ~20° /s; Tilt: 0.5° ~10° /s
	Guard Position	Support
Network Services	Protocol	HTTP/RTSP/FTP/NFS/SNMP/DHCP/NTP, etc.
	Web	IE , Firefox, etc.
	Media	CMS, Android, IOS
	ONVIF	17.06 compatible
General	Network Port	1-RJ45, 100Mbps, POE optional
	Power Supply	12 VDC ± 10%
	Power Consumption	< 10 W
	Operating Temp.	-20℃-(+60)℃, 10%-90%RH