

SV-633E06



Dimensions

Product Summary

- 1/2.7" CMOS sensor
- 3MP HD resolution 2304 x 1296 output
- Ultra low illumination 0.01Lux
- Day/Night, AWB, 2D/3D-DNR, IR-CUT
- Multiply Style OSD Overlay, Motion Detection, Privacy Mask
- RTSP and Onvif 17.06 compatible with many third-party NVR
- H.264/H.265 dual-stream media server
- Easy-to-use P2P Cloud service
- Support user authentication, video data encryption
- Multiply WEB browser IE, Firefox 32bit ESR, PC Client, Mobile APP remote access
- RJ45 100mbps network port, IEEE802.3af PoE
- Lightning protection 4000V
- Strong water-proof housing, IP66
- 12 pcs IR Leds, IR distance 10 meters
- HD 3.7 mm fixed pinhole lens

Major Specifications

* Specifications are subject to change without prior notice.

Model Name		SV-633E06
Camera	Image Sensor	1/2.7" 3MP CMOS
	Effective Pixels	2304(H)×1296 (V)
	Electronic Shutter	AUTO, 1/25s ~ 1/100000s
	Min. Illumination	0.01Lux@F1.2(AGC ON), 0Lux IR on
	Day/Night	Auto/Color/(B/W)/Timing
	White Balance	Auto
	AGC	Support
	DNR	2D/3D DNR
	WDR	D-WDR/HDR
	Other	Multi-lines OSD, Motion Detection, Privacy Mask
Encode	Video Standard	H.264/H.265
	Video Resolution	Main Stream: 25fps@3MP,30fps@1080P/720P Sub Stream: D1/VGA(640x480)/360P/QVGA@30fps
	Video Bitrates	32Kbps - 8Mbps, VBR/CBR
	Audio Standard	G.711-u/G.711-a
	Built-in Mic	Optional
	OSD Overlay	Title and Time overlay
IR Led	IR Led	12 pcs IR Led
	IR Distance	10 M
Lens	Focal length	3.7 mm pinhole fixed lens
Optional Function		POE
Network Services	Protocol	HTTP/RTSP/DHCP/NTP, etc.
	P2P	Yes
	Web	IE , Firefox (32bit esr), etc.
	Media	CMS, Android, IOS
	ONVIF	17.06 compatible
General	Network Port	1-RJ45, 100Mbps, POE optional
	Power Supply	12 VDC ± 10%
	Power Consumption	< 8 W
	Operating Temp.	-30℃-(+60)℃, 10%-90%RH