


# SV-695C97A



## Dimensions



## Product Summary

- 1/2.8" Sony IMX335 CMOS sensor
- Full HD resolution 2592 x 1944P
- Ultra low illumination 0.01Lux
- Day/Night (ICR), AWB, AGC, BLC, 2D/3D-DNR, IR-CUT
- D-WDR, Motion Detection, Privacy Mask, Mirror
- RTSP and Onvif 17.06 compatible
- H.265/H.264 dual-stream media server
- Easy-to-use P2P Cloud service
- Multi web browser, PC Client, mobile APP remote access
- Internal Microphone, reset button optional
- Lightning protection 4000V
- RJ45 100mbps network port, IEEE802.3af PoE
- Strong water-proof housing, IP67
- 2PCS Soft & Warm Supplemental Light, Light distance: 25-30M
- HD 2.8mm F1.0 true starlight lens

## Major Specifications

\* Specifications are subject to change without prior notice.

Model Name		SV-695C97A
Camera	Image Sensor	1/2.8" SONY IMX335 CMOS
	Effective Pixels	2592 (H) × 1944 (V)
	Electronic Shutter	AUTO, 1/25s ~ 1/100000s
	Min. Illumination	0.001Lux@F1.2(AGC ON), 0Lux IR on
	Day/Night	Auto/Color/(B/W)/Timing
	WDR	Digital WDR
	White Balance	Auto/Indoor/Outdoor
	BLC	Support
	DNR	2D/3D DNR
Other	Motion Detection, Privacy Mask, Mirror, flip	
Encode	Embedded Solution	SSC337
	Video Standard	H.264/H.265
	Video Resolution	Main Stream: 25fps@ 5MP(2592*1944) Sub Stream: VGA(640x480)/360P@25fps, etc.
	Video Bitrates	32Kbps - 6Mbps, VBR/CBR
	Audio Standard	G.711-u/G.711-a
	OSD Overlay	Title and Time overlay
Leds	Leds	2PCS Soft & Warm Supplemental Light
	Light Distance	25-30 M
Lens	Focal length	HD 2.8mm F1.0 true starlight lens
Optional Function		Audio
Network Services	Protocol	HTTP/RTSP/FTP/NFS/SMTP/DHCP/NTP, etc.
	P2P	Yes
	Web	IE, Firefox, etc.
	Media	CMS, Android, IOS
General	ONVIF	17.06 compatible
	Network Port	1-RJ45, 100Mbps,
	Power Supply	IEEE802.3af PoE, 12 VDC ± 10%
	Power Consumption	< 8 W
Operating Temp.		-30℃-(+60)℃, 10%-90%RH