

SVK-1600S



Product Summary

- 16CH 4K UHD(Coaxial)
- H.265 Compression
- UHD(3840x2160)Real-time Recording per CH
- Display up to 4K(3840x2160) on HDMI
- Digital Zoom in/Out On Live& Playback
- Network Time Protocol
- User Friendly Interface
- Mobile Viewer
- CMS
- Size : 430mm(W) x 65mm(H) x 330mm(D)

Major Specifications

Model Name		SVK-1600S
Video	Input Channel / Type	16CH / 8M (4K UHD) @30fps per CH
	Output Main	HDMI (Max 3840x2160)
	Output Sub	CVBS or SPOT (Selectable)
Audio	Input / Output	Local : 4in / 1 out
	Codec	G.711
Alarm	Sensor Input	Local : 4
	Alarm Out	Local : 1
	RS-485	Yes
Recording	Compression	H.265
	4K Input	Max. 2160p@25/30 fps/channel (3840X2160 Resolution)
	1920x1080 Input	Max. 1080p@25/30fps/channel
	1280x720 Input	Max. 720p@25/30fps/channel
	Recording Quality	5 Levels
	Recording Mode	Continuous / Schedule / Motion / Sensor / Manual
	Pre Recording	Min. 15 Seconds / Max. 20 Minutes
	Post Recording	Max. 60 Seconds
Playback	Search Mode	Timeline / Event / Archive / Log / Specific Time
Backup	File Format	BMP, AVI, EXE(Player+Data), NSF(Proprietary Format)
	Media	USB/External HDD/Network (Huge Backup Max. 24 hours)
	Viewer	Built-in
Storage	Max. Capacity	6TB / SATA HDD
	Max. HDD	Max 3EA internal
	ODD	N/A
	External Storage	1 e-SATA
	USB	2ea
Features	Digital Zoom	Live and Playback, Free Size
	DST	EU and USA
	NTP	Yes
	S.M.A.R.T	Yes
	Internal Beep	Yes
	Multi-Language	Yes
	e-mail Notification	Yes
Network	Interface	10/100/1000 Base-TX
	Dynamic DNS	Free DDNS
	Dual Encoding for Network	Yes (Max. 1024X720)
	3G/4G Mobile	iPad / iPhone / Android
	Web Viewer	Windows (IE, Chrome, Firefox, Safari)
	PC Client	Single / Multi Client and CMS (64 channels)
	Remote Setup	Web Setup
	Upgrade	Web Setup
Power		DC12V 5A
Dimension		430mm(W) x 65mm(H) x 330mm(D)