


## SVNI10171XR



## Dimensions



## Product Summary

- 6.4 Mega pixel 1/1.8" SONY STAVIS progressive scan CMOS
- 30M IR Beam Distance
- Triple Stream
- Supports image resolution up to 5MP
- Supports VBR/CBR in H.264
- Controllable frame rate
- Supports WDR, Defog, 2D+3DNR, Smart IR
- Corridor view in H.264
- Tool-Free 3-Axis
- 12VDC/ IEEE802.3af POE
- Conformant with ONVIF (Profile-S)
- Includes Windows based IP Installer and license-free 16 channel NVR(Network Video Recorder) software

## Major Specifications

\* OSD Menu is subject to change without prior notice

MODEL	SVNI10171XR
CPU	ARM1176JZF-S (400 MHz, Instruction cache: 32kbyte, data cache)
Flash	2Gbit Flash memory
SDRAM	2Gbit DDR3
Image sensor	6.4 Mega 1/1.8" SONY STAVIS progressive scan CMOS
Total Pixels	3096(H) x 2094(V) 6.48 Megapixel
Effective Pixels	3089(H) x 2064(V) 6.38 Megapixel
S/N Ratio	More than 50dB
Min. Illumination	0 Lux (IR On)
IR Distance	30M (4 Built-in Power LED's)
Day & Night	ICR
Lens	2.8mm Wide angle Megapixel Board Lens
Video compression	H.264 High Profile, MJPEG
Resolutions	Up to 2592 x 1944 5MP
Frame rate	Triple Stream / 1st stream: 15fps@2592 x 1944 2nd stream: 30fps@640 x 480 ,3rd stream: 30fps@640x480
Video streaming	Triple stream with H.264/MJPEG, Adjustable frame rate, CBR/VBR in H.264
Pan/Tilt/Zoom	Digital PTZ
Corridor view	Corridor view in H.264 (90degree/ 270degree)
Image setting	Brightness, contrast, Sharpness,Day & Night,Auto White Balance Auto Exposure,Privacy Mask,DSS, Effect - Color, Mirror/V-Flip, etc.
Security	Password Protection, User access log, HTTPS encryption
Supported protocol	HTTP, HTTPS, FTP, SMTP, UPnP, DNS, DDNS, NTP, RTSP, RTP, TCP, UDP, ICMP, DHCP
Intelligent video	Object based Motion detection up with 12x 12 block Tamper detection with Global scene change and defocus.
Alarm events	File upload via ftp, E-mail, Notification via email,SD Card.
Video buffer	5MB pre-alarm and 180 sec (max) post-alarm
Firmware upgrade	Remote upgrade via network
API	CGI Interface document, ActiveX Interface(ocx(dll) + document)
Power Source	DC12V/1.5A, PoE(Power over Ethernet): 802.3af-Optional
Power Consumption	Max. 5W with IR
Net Weight	280g (Camera only)
LED's	Power, Network Connection
Dimension	130mm(Dia.) x77mm
Operating Temperature	-10 degree~50 degree Celsius(14F~122F)
Storage Temperature	-20 degree~60 degree Celsius(-4F~140F)
Included Software	NVR C/S (16 Channel), IP Installer (Windows only)