

SVR-1004NFA



Product Summary

- 1080P (1920x1080P) 120fps Recording.
- 1080P, 720P, 960H selectable.
- Various video output port (HDMI, VGA, BNC)
- Various video output mode (Full HD,XGA, SDTV)
- Internal HDD 2ea or 1 HDD + 1 eSATA
- ONVIF
- Video clip (Backup viewer),
JPEG Still Image, Log list, Setup data
- Covert channel, Private Zone
- Apple Mac OS
- iPhone, Android, iPad
- 4 PoE

Major Specifications

Model Name		SVR-1004NFA
System	OS	Embedded Linux
	Language	Chinese, Chinese(S), Dutch, English, French, German, Hebrew, Hungari, Italian, Japanese, Korean, Latvian, Persian, Polish, Portuguese, Russian, Spanish, Sweden, Turkish
	Time Accuracy	5ppm (12.5sec/month)
	Time Sync.	NTP, GMT, DST
	User	15 Users (Admin., User1 ~ User14)
	Access	Front button, Mouse, Remocon, Network, Key controller
Camera	Hexaplex Upgrade	Live monitoring, Recording, Playback, Backup, Network, Setup
	IP Camera	USB2.0 Memory stick, Network
Video	System	ONVIF
	Input	NTSC / PAL - Config switch
	Display Rate	4ch
	Output Interface	Max. 1080p 120/100fps (Max. D1 480/400fps)
	Output Resolution	HDMI, VGA, BNC
Audio	Spot	Full HD
	Input Interface	N/A
Video Recording	Output Interface	16 IPC
	Compression	HDMI
	Speed	H.264
	Resolution	Max.120fps
Audio Recording	Mode	Max. 2MP/ch
	Event	Schedule
	Bit Rate	Motion, Local Sensor
Playback	Compression	64Mbps
	Audio Sampling Rate	G.711
Network	Audio Bit Rate	Depends on IPC
	Search	Depends on IPC
Backup	Mode	Go to first rec. time, Go to last rec. time, Go to last search time, Calenda, Log viewer, Smart search, Multi-time & day search, Event search
	Interface	Event only playback, Backward, Pause, Frame by frame, Speed up (x1 ~ x32, x300)
	Compression	RJ45 (Ethernet 10/100/1G) x 1
Bootling	Speed	H.264
	Resolution	Max. D1 30fps in total
Alarm	Interface	Max. 1080p
	Format	USB2.0, Network
Display	Live	Video clip (Backup viewer), JPEG Still Image, Log list, Setup data
	Recording	40sec
	Post-Alarm	50sec
	Motion Grid	5sec~5min
External Interface	Alarm Action	14x15 (NTSC/PAL)
	Input / Output	E-mail, Event Popup, Buzzer, Relay, Preset, Remote CMS, Front LED
Storage	HDMI	4/1 - EOL
	VGA	Full HD
	TV	Full HD
Features	Mode	SDTV(720x480/576)
	Camera Title Name	16/9/4/1/SEQ/BIG - LIVE, 16/9/4/1 - P.B
	PTZ / Keyboard	English : 20 characters, Chinese, Japanese, Korean : 10 characters
	ATM/POS	2 RS485 - Terminal Block
	Primary	RS232C - Terminal Block, Ethernet POS
	External	2 HDD or 1 HDD
	ODD	1 eSATA
	POE	N/A
	Jog-shuttle	N/A
	HW RAID	N/A
Electrical	EOL	N/A
	Digital Zoom	Yes
	Watermarking	x1 ~ x16
	Two-way Audio	Yes
	Detection / Search	N/A
	Fan Fail	Motion, Sensor
	E-mail	Yes
	Capture	5 User
	iSCS Recording	1080p
	DDNS, DHCP, UPNP	Yes
	CMS, VMS, RMS	Yes
	Smart Phone (3G)	Windows
Mac Viewer	Android, iPhone, iPad	
General	Input Voltage (DVR)	Apple Mac OS
	Input Voltage (PoE)	DC 12V, 5A
	Camera Power Output	54xx series : DC48V / 1A, 58xx series : DC48V / 2A 51xx : N/A, 54xx : Max. 30 W per channel, Up to Total 40W, 58xx : Max. 30 W per channel, Up to Total 80W
General	Power Supply	12V/5A - Level 5
	Operating Temp.	5 ~ 40 °C
	Humidity	10 ~ 80%
	Weight w/o HDD	3Kg
	Dimension	340 x 59 x 300 mm
Certification	CE, FCC, RoHS Compliance	