

SVR-1008NEA



Product Summary

- 1080P (1920x1080P) 240fps Recording.
- 1080P, 720P, 960H selectable.
- Various video output port (HDMI, VGA, BNC)
- Various video output mode (Full HD, XGA, SDTV)
- Internal HDD 2ea or 1 HDD + 1 eSATA
- ONVIF
- Video clip (Backup viewer), JPEG Still Image, Log list, Setup data
- Covert channel, Private Zone
- Apple Mac OS
- iPhone, Android, iPad
- 8 PoE

Major Specifications

Model Name	SVR-1008NEA	
System	OS	Embedded Linux
	Language	Chinese, Chinese(S), Dutch, English, French, German, Hebrew, Hungari, Italian, Japanese, Korean, Latvian, Persian, Polish, Portuguese, Russian, Spanish, Sweden, Turkish
	Time Accuracy	5ppm (12.5sec/month)
	Time Sync.	NTP, GMT, DST
	User	15 Users (Admin., User1 ~ User14)
Camera	Access	Front button, Mouse, Remocon, Network, Key controller
	Hexaplex Upgrade	Live monitoring, Recording, Playback, Backup, Network, Setup
	IP Camera	USB2.0 Memory stick, Network
Video	System	ONVIF
	Input	NTSC / PAL - Config switch
	Display Rate	8ch
	Output Interface	Max. 1080p 120/100fps (Max. D1 480/400fps)
Audio	Output Resolution	HDMI, VGA, BNC
	Spot	Full HD
	Input Interface	N/A
Video Recording	Output Interface	16 IPC
	Compression	H.264
	Speed	Max.240fps
	Resolution	Max.2MP/ch
Audio Recording	Mode	Schedule
	Event	Motion, Local Sensor
	Bit Rate	64Mbps
Playback	Compression	G.711
	Audio Sampling Rate	Depends on IPC
Network	Audio Bit Rate	Depends on IPC
	Search	Go to first rec. time, Go to last rec. time, Go to last search time, Calenda, Log viewer, Smart search, Multi-time & day search, Event search
Backup	Mode	Event only playback, Backward, Pause, Frame by frame, Speed up (x1 ~ x32, x300)
	Interface	RJ45 (Ethernet 10/100/1G) x 1
	Compression	H.264
Booting	Speed	Max. D1 30fps in total
	Resolution	Max. 1080p
Alarm	Interface	USB2.0, Network
	Format	Video clip (Backup viewer), JPEG Still Image, Log list, Setup data
Display	Live	40sec
	Recording	50sec
	Post-Alarm	5sec~5min
	Motion Grid	14x15 (NTSC/PAL)
Storage	Alarm Action	E-mail, Event Popup, Buzzer, Relay, Preset, Remote CMS, Front LED
	Input / Output	4/1 - EOL
	HDMI	Full HD
	VGA	Full HD
	TV	SDTV(720x480/576)
External Interface	Mode	16/9/4/1/SEQ/BIG - LIVE, 16/9/4/1 - P.B
	Camera Title Name	English : 20 characters, Chinese, Japanese, Korean : 10 characters
Features	PTZ / Keyboard	2 RS485 - Terminal Block
	ATM/POS	RS232C - Terminal Block, Ethernet POS
	Primary	2 HDD or 1 HDD
Electrical	External	1 eSATA
	ODD	N/A
	POE	8PoE
	Jog-shuttle	N/A
	HW RAID	N/A
	EOL	Yes
	Digital Zoom	x1 ~ x16
	Watermarking	Yes
	Two-way Audio	N/A
	Detection / Search	Motion, Sensor
	Fan Fail	Yes
	E-mail	5 User
	Capture	1080p
	iSCS Recording	Yes
	DDNS, DHCP, UPNP	Yes
CMS, VMS, RMS	Windows	
Smart Phone (3G)	Android, iPhone, iPad	
Mac Viewer	Apple Mac OS	
General	Input Voltage (DVR)	DC 12V, 5A
	Input Voltage (PoE)	54xx series : DC48V / 1A, 58xx series : DC48V / 2A
	Camera Power Output	51xx : N/A, 54xx : Max. 30 W per channel, Up to Total 40W, 58xx : Max. 30 W per channel, Up to Total 80W
General	Power Supply	12V/5A - Level 5
	Operating Temp.	5 ~ 40 °C
	Humidity	10 ~ 80%
	Weight w/o HDD	3Kg
	Dimension	340 x 59 x 300 mm
Certification	CE, FCC, RoHS Compliance	