

SVR-1016NA



Product Summary

- 1080P (1920x1080P) 480fps Recording.
- 1080P, 720P, 960H selectable.
- Various video output port (HDMI, VGA, BNC)
- Various video output mode (Full HD, XGA, SDTV)
- Internal HDD 2ea or 1 HDD + 1 eSATA
- ONVIF
- Video clip (Backup viewer),
JPEG Still Image, Log list, Setup data
- Covert channel, Private Zone
- Apple Mac OS
- iPhone, Android, iPad

Major Specifications

Model Name		SVR-1016NA
System	OS	Embedded Linux
	Language	Chinese, Chinese(S), Dutch, English, French, German, Hebrew, Hungari, Italian, Japanese, Korean, Latvian, Persian, Polish, Portuguese, Russian, Spanish, Sweden, Turkish
	Time Accuracy	5ppm (12.5sec/month)
	Time Sync.	NTP, GMT, DST
	User	15 Users (Admin., User1 ~ User14)
	Access	Front button, Mouse, Remocon, Network, Key controller
Camera	Hexaplex Upgrade	Live monitoring, Recording, Playback, Backup, Network, Setup
	IP Camera	USB2.0 Memory stick, Network
Video	System	ONVIF
	Input	NTSC / PAL - Config switch
	Display Rate	16ch
	Output Interface	Max. 1080p 480/400fps
Audio	Output Resolution	HDMI, VGA, BNC
	Spot	Full HD
	Input Interface	N/A
	Output Interface	16 IPC
Video Recording	Compression	H.264
	Speed	Max. 480fps/400fps
	Resolution	Max.2MP/ch
	Mode	Schedule
Audio Recording	Event	Motion, Local Sensor
	Bit Rate	64Mbps
	Compression	G.711
	Audio Sampling Rate	Depends on IPC
Playback	Search	Depends on IPC
	Mode	Go to first rec. time, Go to last rec. time, Go to last search time, Calenda, Log viewer, Smart search, Multi-time & day search, Event search
Network	Interface	Event only playback, Backward, Pause, Frame by frame, Speed up (x1 ~ x32, x300)
	Compression	RJ45 (Ethernet 10/100/1G) x 2
	Speed	H.264
Backup	Resolution	Max. D1 30fps in total
	Interface	Max. 1080p
Bootling	Format	USB2.0, Network
	Live	Video clip (Backup viewer), JPEG Still Image Log list, Setup data
Alarm	Recording	40sec
	Post-Alarm	50sec
	Motion Grid	5sec~5min
	Alarm Action	14x15 (NTSC/PAL)
Display	Input / Output	E-mail, Event Popup, Buzzer, Relay, PTZ Preset, Remote CMS, Front LED
	HDMI	4/1 - EOL
	VGA	Full HD
	TV	Full HD
External Interface	Camera Title Name	SDTV(720x480/576)
	PTZ / Keyboard	16/9/4/1/SEQ/BIG - LIVE, 16/9/4/1 - P.B
Storage	ATM/POS	English : 20 characters Chinese, Japanese, Korean : 10 characters
	Primary	2 RS485 - Terminal Block
	External	RS232C - Terminal Block, Ethernet POS
	ODD	2 HDD or 1 HDD
Features	POE	1 eSATA
	Jog-shuttle	N/A
	HW RAID	N/A
	EOL	N/A
	Digital Zoom	Yes
	Watermarking	x1 ~ x16
	Two-way Audio	Yes
	Detection / Search	N/A
	Fan Fail	Motion, Sensor
	E-mail	Yes
	Capture	5 User
	iSCS Recording	1080p
	DDNS, DHCP, UPNP	Yes
	CMS, VMS, RMS	Yes
	Smart Phone (3G)	Windows
	Mac Viewer	Android, iPhone, iPad
Electrical	Input Voltage (DVR)	Apple Mac OS
	Input Voltage (PoE)	DC 12V, 5A
	Camera Power Output	54xx series : DC48V / 1A, 58xx series : DC48V / 2A 51xx : N/A, 54xx : Max. 30 W per channel, Up to Total 40W, 58xx : Max. 30 W per channel, Up to Total 80W
General	Power Supply	12V/5A - Level 5
	Operating Temp.	5 ~ 40 °C
	Humidity	10 ~ 80%
	Weight w/o HDD	3Kg
	Dimension	340 x 59 x 300 mm
Certification	CE, FCC, RoHS Compliance	