

SVR-2008NE



Product Summary

- 1080P (1920x1080P) 240fps Recording.
- 1080P, 720P, 960H selectable.
- Various video output port (HDMI, VGA, BNC)
- Various video output mode (Full HD,XGA, SDTV)
- RAID 1/5/10 Option.
- Internal HDD 3ea, 1 eSATA
- ONVIF
- Video clip (Backup viewer), JPEG Still Image, Log list, Setup data
- Covert channel, Private Zone
- Apple Mac OS
- iPhone, Android, iPad
- 8 PoE

Major Specifications

Model Name		SVR-2008NE
System	OS	Embedded Linux
	Language	Chinese, Chinese(S), Dutch, English, French, German, Hebrew, Hungari, Italian, Japanese, Korean, Latvian, Persian, Polish, Portuguese, Russian, Spanish, Sweden, Turkish
	Time Accuracy	5ppm (12.5sec/month)
	Time Sync.	NTP, GMT, DST
	User	15 Users (Admin., User1 ~ User14)
	Access	Front button, Mouse, Remocon, Network, Key controller
Camera	Hexaplex Upgrade	Live monitoring, Recording, Playback, Backup, Network, Setup
	IP Camera	USB2.0 Memory stick, Network
	System	ONVIF
Video	Input	NTSC / PAL - Config switch
	Display Rate	8ch
	Output Interface	Max. 1080p 120/100fps (Max. D1 480/400fps)
	Output Resolution	HDMI, VGA, BNC
Audio	Spot	Full HD
	Input Interface	N/A
	Output Interface	16 IPC
Video Recording	Compression	H.264
	Speed	Max.240fps/200fps
	Resolution	Max.5MP/ch
	Mode	Schedule
	Event	Motion, Local Sensor
Audio Recording	Bit Rate	64Mbps
	Compression	G.711
	Audio Sampling Rate	Depends on IPC
Playback	Search	Depends on IPC
	Mode	Go to first rec. time, Go to last rec. time,Go to last search time,Calenda, Log viewer, Smart search,Multi-time & day search, Event search
Network	Interface	Event only playback, Backward,Pause, Frame by frame, Speed up (x1 ~ x32, x300)
	Compression	RJ45 (Ethernet 10/100/1G) x 1
	Speed	H.264
Backup	Resolution	Max. D1 30fps in total
	Interface	Max. 1080p
Bootling	Format	USB2.0, DVD, Network
	Live Recording	Video clip (Backup viewer), JPEG Still Image, Log list, Setup data
Alarm	Post-Alarm	40sec
	Motion Grid	50sec
	Alarm Action	5sec~5min
	Input / Output	14x15 (NTSC/PAL)
Display	HDMI	E-mail, Event Popup, Buzzer, Relay, Preset,Remote CMS, Front LED
	VGA	4/1 - EOL
	TV Mode	Full HD
External Interface	Camera Title Name	Full HD
	PTZ / Keyboard	SDTV(720x480/576)
Storage	ATM/POS	16/9/4/1/SEQ/BIG - LIVE, 16/9/4/1 - P.B
	Primary	English : 20 characters, Chinese, Japanese, Korean : 10 characters
	External	2 RS485 - Terminal Block
Features	POE	RS232C - Terminal Block, Ethernet POS
	Jog-shuttle	3 HDD
	HW RAID	1 eSATA
	EOL	1 DVD
	Digital Zoom	8PoE
	Watermarking	N/A
	Two-way Audio	RAID1/5/10 Options
	Detection / Search	Yes
	Fan Fail	x1 ~ x16
	E-mail	Yes
	Capture	N/A
	iSCS Recording	Motion, Sensor
	DDNS, DHCP, UPNP	Yes
	CMS, VMS, RMS	Yes
Smart Phone (3G)	5 User	
Mac Viewer	1080p	
Electrical	Input Voltage (DVR)	Yes
	Input Voltage (PoE)	Yes
	Camera Power Output	100W
General	Power Supply	Windows
	Operating Temp.	Android, iPhone, iPad
	Humidity	Apple Mac OS
	Weight w/o HDD	DC 12V, 5A
	Dimension	54xx series : DC48V / 1A, 58xx series : DC48V / 2A
Certification	51xx : N/A, 54xx : Max. 30 W per channel, Up to Total 40W, 58xx : Max. 30 W per channel, Up to Total 80W	