

SVR-3004NFA



Product Summary

- 1080P (1920x1080P) 120fps Recording.
- 1080P, 720P, 960H selectable.
- Various video output port (HDMI, VGA, BNC)
- Various video output mode (Full HD,XGA, SDTV)
- RAID 1/5/10 Option.
- Internal HDD 6ea, 2 eSATA
- ONVIF
- Video clip (Backup viewer), JPEG Still Image, Log list, Setup data
- Covert channel, Private Zone
- Apple Mac OS
- iPhone, Android, iPad
- 4 PoE

Major Specifications

Model Name		SVR-3004NFA
System	OS	Embedded Linux
	Language	Chinese, Chinese(S), Dutch, English, French, German, Hebrew, Hungari, Italian, Japanese, Korean, Latvian, Persian, Polish, Portuguese, Russian, Spanish, Sweden, Turkish
	Time Accuracy	5ppm (12.5sec/month)
	Time Sync.	NTP, GMT, DST
	User	15 Users (Admin., User1 ~ User14)
	Access	Front button, Mouse, Remocon, Network, Key controller
Camera	Hexaplex	Live monitoring, Recording, Playback, Backup, Network, Setup
	Upgrade	USB2.0 Memory stick, Network
	IP Camera System	ONVIF
Video	Input	NTSC / PAL - Config switch
	Display Rate	4ch
	Output Interface	Max. 1080p 120/100fps (Max. D1 480/400fps)
Audio	Output Interface	HDMI, VGA, BNC
	Spot	Full HD
	Input Interface	N/A
Video Recording	Output Interface	16 IPC
	Compression	HDMI
	Speed	H.264
	Resolution	Max.120fps
Audio Recording	Mode	Max. 2MP/ch
	Event	Schedule
	Bit Rate	Motion, Local Sensor
	Compression	64Mbps
Playback	Audio Sampling Rate	G.711
	Audio Bit Rate	Depends on IPC
	Search	Depends on IPC
Network	Search	Go to first rec. time, Go to last rec. time,Go to last search time,Calenda, Log viewer, Smart search,Multi-time & day search, Event search
	Mode	Event only playback, Backward,Pause, Frame by frame, Speed up (x1 ~ x32, x300)
	Interface	RJ45 (Ethernet 10/100/1G) x 1
Backup	Compression	H.264
	Speed	Max. D1 30fps in total
	Resolution	Max. 1080p
Booting	Interface	USB2.0, DVD, Network
	Format	Video clip (Backup viewer), JPEG Still Image, Log list, Setup data
	Live	40sec
Alarm	Recording	50sec
	Post-Alarm	5sec~5min
	Motion Grid	14x15 (NTSC/PAL)
	Alarm Action	E-mail, Event Popup, Buzzer, Relay, Preset,Remote CMS, Front LED
Display	Input / Output	4/1 - EOL
	HDMI	Full HD
	VGA	Full HD
External Interface	TV	SDTV(720x480/576)
	Mode	16/9/4/1/SEQ/BIG - LIVE, 16/9/4/1 - P.B
	Camera Title Name	English : 20 characters,Chinese, Japanese, Korean : 10 characters
Storage	PTZ / Keyboard	2 RS485 - Terminal Block
	ATM/POS	RS232C - Terminal Block, Ethernet POS
	Primary	6 HDD
Features	External	2 eSATA
	ODD	1 DVD
	POE	4 PoE
	Jog-shuttle	Yes
	HW RAID	RAID1/5/10 Options
	EOL	Yes
	Digital Zoom	x1 ~ x16
	Watermarking	Yes
	Two-way Audio	N/A
	Detection / Search	Motion, Sensor
	Fan Fail	Yes
	E-mail	5 User
	Capture	1080p
	iSCS Recording	Yes
	DDNS, DHCP, UPNP	Yes
	CMS, VMS, RMS	Windows
Smart Phone (3G)	Android, iPhone, iPad	
Mac Viewer	Apple Mac OS	
Electrical	Input Voltage (DVR)	AC 90V ~ 250V, 50/60Hz
	Input Voltage (PoE)	54xx series : DC48V / 1A, 58xx series : DC48V / 2A
	Camera Power Output	51xx : N/A, 54xx : Max. 30 W per channel, Up to Total 40W, 58xx : Max. 30 W per channel, Up to Total 80W
General	Power Supply	90~250V, 50/60Hz
	Operating Temp.	5 ~ 40 °C
	Humidity	10 ~ 80%
	Weight w/o HDD	8Kg
Certification	Dimension	440 x 88 x 430 mm
		CE, FCC, RoHS Compliance