

SVR- 4004AM**Product Summary**

- Embedded Linux - Built in flash memory
- USB2.0 Memory stick, Network
- 16, 8, 4 BNC
- 5ppm (12.5sec/month)
- 15 Users (Admin., User1 ~ User14)
- NTP, GMT, DST, Time Server

Major Specifications

Model Name		SVR- 4004AM
System	OS	Embedded Linux - Built in flash memory
	Language	Chinese, Chinese(S), Dutch, English,French, German, Hebrew, Hungari,Italian, Japanese, Korean, Latvian,Persian, Polish, Portuguese, Russian,Spanish, Sweden, Turkish
	Time Accuracy	5ppm (12.5sec/month)
	Time Sync.	NTP, GMT, DST, Time Server
	User	15 Users (Admin., User1 ~ User14)
	Access	Front button, Mouse, Remocon, Network, Key controller
	Hexaplex Upgrade	Live monitoring, Recording, Playback, Backup, Network, Setup
Video	System	USB2.0 Memory stick, Network
	Input	NTSC / PAL - Config switch
	Output	4 BNC
	Loop	1 HDMI, 1 VGA, 1 BNC
Audio	Spot	4 BNC
	Input	1 BNC
Video Recording	Output	4 RCA
	Compression	1 RCA
	Speed	H.264
	Resolution	AHD : 30fps/ch, 960H : 30fps/ch
	Mode	AHD : 720P , 960H : 960H, D1, CIF
	Event	Schedule, Watermark
	Quality	Sensor, Motion, Audio, Text
Audio Recording	Bit Rate	5 Levels
	Compression	512Kbps ~ 3Mbps/Ch, Adjustable
	Audio Sampling Rate	G.711u
Playback	Audio Bit Rate	8KHz
	Search	32Kbps
Network	Mode	Go to first rec. time, Go to last rec. time, Go to last search time, Calenda, Log viewer, Smart search, POS Search, Multi-time & day search, Event search
	Interface	Event only playback, Backward, Pause, Frame by frame, Panaloma Speed up (x1 ~ x32, x300)
	Compression	Ethernet 10/100/1G
	Speed	H.264 or JPEG
Backup	Resolution	Max. 720P 10fps/ch
	Mode	Max. 720p
Bootling	Interface	Bandwidth control
	Format	USB2.0, DVD, Network
Alarm	Recording	Video clip (Backup viewer), JPEG Still Image, Log list, Setup data
	Pre/Post-Alarm	16sec
	Motion Grid	40sec
Display	Alarm Action	5sec / 5sec~5min
	Input / Output	14 x 15
	HDMI	E-mail, Channel Popup, Buzzer, Relay, PTZ Preset, Spot, Remote CMS, Front LED
	VGA	16/4, 8/2, 4/1 - NC/NO/EOL
External Interface	TV	Full HD, XGA
	Mode	Full HD, XGA
	Camera Adjust	SDTV(720x480/576)
	Camera Title Name	16/9/4/1/SEQ - LIVE, 16/9/4/1 - P.B
	PTZ / Keyboard	Left, Right, Up, Down, Brightness, Contrast, Hue, Saturation, Sharpness
	ATM / POS	English : 20 characters, Chinese, Japanese, Korean : 10 characters
	Primary	2 RS485 - Terminal Block
Storage	External	RS232C - Terminal Block, Ethernet POS
	ODD	3 HDD
	H/W RAID	1 eSATA
	EOL	1 DVD
	Coaxiltron	H/W RAID5/1 Options
	Privacy Zone	4Ch
	Covert Channel	Pelco Protocol
	Digital Zoom	Yes
	Watermarking	Yes
	Two-way Audio	Yes
General	Detection / Search	Motion, Sensor, Audio, Text
	Fan Fail	Yes
	E-mail	5 User with still image
	Capture	1080p, XGA
	iSCS Recording	Yes
	DDNS, DHCP, UPNP	Yes
	CMS, VMS, RMS	Windows
	Smart Phone (3G)	Android, iPhone, iPad
	Mac Viewer	Apple Mac OS
	Power Supply	12V/5A - Level 5
	Consumption	60Watts
	Operating Temp.	5 ~ 40 °C
	Humidity	10 ~ 80%
Weight w/o HDD	4Kg	
Dimension	430 x 86 x 270 mm	
Certification	CE, FCC, RoHS Compliance	