

SVR- 4008AM



Product Summary

- Embedded Linux - Built in flash memory
- USB2.0 Memory stick, Network
- 16, 8, 4 BNC
- 5ppm (12.5sec/month)
- 15 Users (Admin., User1 ~ User14)
- NTP, GMT, DST, Time Server

Major Specifications

Model Name		SVR-4008AM
System	OS	Embedded Linux - Built in flash memory
	Language	Chinese, Chinese(S), Dutch, English, French, German, Hebrew, Hungari, Italian, Japanese, Korean, Latvian, Persian, Polish, Portuguese, Russian, Spanish, Sweden, Turkish
	Time Accuracy	5ppm (12.5sec/month)
	Time Sync.	NTP, GMT, DST, Time Server
	User	15 Users (Admin., User1 ~ User14)
	Access	Front button, Mouse, Remocon, Network, Key controller
	Hexaplex	Live monitoring, Recording, Playback, Backup, Network, Setup
Video	Upgrade	USB2.0 Memory stick, Network
	System	NTSC / PAL - Config switch
	Input	8BNC
	Output	1 HDMI, 1 VGA, 1 BNC
Audio	Loop	8BNC
	Spot	1 BNC
	Input	8RCA
Video Recording	Output	1 RCA
	Compression	H.264
	Speed	AHD : 30fps/ch, 960H : 30fps/ch
	Resolution	AHD : 720P , 960H : 960H, D1, CIF
	Mode	Schedule, Watermark
	Event	Sensor, Motion, Audio, Text
Audio Recording	Quality	5 Levels
	Bit Rate	512Kbps ~ 3Mbps/Ch, Adjustable
	Compression	G.711u
Playback	Audio Sampling Rate	8KHz
	Audio Bit Rate	32Kbps
	Search	Go to first rec. time, Go to last rec. time, Go to last search time, Calenda, Log viewer, Smart search, POS Search, Multi-time & day search, Event search
Network	Mode	Event only playback, Backward, Pause, Frame by frame, Panaloma Speed up (x1 ~ x32, x300)
	Interface	Ethernet 10/100/1G
	Compression	H.264 or JPEG
	Speed	Max. 720P 10fps/ch
Backup	Resolution	Max. 720p
	Mode	Bandwidth control
	Interface	USB2.0, DVD, Network
Booting	Format	Video clip (Backup viewer), JPEG Still Image, Log list, Setup data
	Live	16sec
Alarm	Recording	40sec
	Pre/Post-Alarm	5sec / 5sec~5min
	Motion Grid	14 x 15
	Alarm Action	E-mail, Channel Popup, Buzzer, Relay, PTZ Preset, Spot, Remote CMS, Front LED
	Input / Output	16/4, 8/2, 4/1 - NC/NO/EOL
Display	HDMI	Full HD, XGA
	VGA	Full HD, XGA
	TV	SDTV(720x480/576)
	Mode	16/9/4/1/SEQ - LIVE, 16/9/4/1 - P.B
External Interface	Camera Adjust	Left, Right, Up, Down, Brightness, Contrast, Hue, Saturation, Sharpness
	Camera Title Name	English : 20 characters, Chinese, Japanese, Korean : 10 characters
	PTZ / Keyboard	2 RS485 - Terminal Block
Storage	ATM / POS	RS232C - Terminal Block, Ethernet POS
	Primary	3 HDD
	External	1 eSATA
	ODD	1 DVD
General	H/W RAID	H/W RAID5/1 Options
	EOL	4Ch
	Coaxiltron	Pelco Protocol
	Privacy Zone	Yes
	Covert Channel	Yes
	Digital Zoom	x1 ~ x16
	Watermarking	Yes
	Two-way Audio	Yes
	Detection / Search	Motion, Sensor, Audio, Text
	Fan Fail	Yes
	E-mail	5 User with still image
	Capture	1080p, XGA
	iSCS Recording	Yes
	DDNS, DHCP, UPNP	Yes
	CMS, VMS, RMS	Windows
	Smart Phone (3G)	Android, iPhone, iPad
	Mac Viewer	Apple Mac OS
	Power Supply	12V/5A - Level 5
	Consumption	60Watts
	Operating Temp.	5 ~ 40 °C
Humidity	10 ~ 80%	
Weight w/o HDD	4Kg	
Dimension	430 x 86 x 270 mm	
Certification	CE, FCC, RoHS Compliance	