

SVR-5004NLI5



Product Summary

- Video Input 04ch IP
- Video Input Resolution Max, 4K
- Video Output 1 HDMI
- Video Output Resolution Max. 4K
- Recording Speed 7.5fps/ch (4K), 30fps/ch (2MP)
- Recording Resolution Max. 4K
- Recording Compression H.265, H.264. JPEG

Major Specifications

*Specifications is subject to change without advanced notice.

Model		SVR-5004NLI5
Video	Input	4IP
	Input Resolution	Max, 4K
	Output	1 HDMI
	Output Resolution	Max. 4K
Recording	Speed	7.5fps/ch (4K), 30fps/ch (2MP)
	Resolution	Max. 4K
	Compression	H.265, H.264. JPEG
Audio	Input	1CH
	Output	1CH
Interface	Senser In / Out	4 IN / 1 OUT
	USB	3 Port(Front 2, Rear1)
	PTZ	RS485 - Terminal Block
Network	Interface	2 x Ethernet 10/100/1G
	Compression	H.265
	Speed	7.5fps(4MP)
	Resolution	Max. 4MP
System	OS	Embedded Linux 4.2 (Built-in Flash Memory)
	Pre / Post-Alarm	5sec / 5sec~5min
	Recording Mode	Continuous, Event, Schedule
	Data Search	Calendar, Multi Day / Time, Event, Go to Time
	Backup Interface	USB, Network
	Backup Type	Video(RMS, AVI), Capture(JPEG), Log List, Setup Data
	Alarm Action	Buzzer, PTZ Preset, E-mail, Event Popup, Push
	User	15 Users (Admin, User1 ~ User14)
	Network Viewer	NETUS-Pro, NETUS-Lite (Windows, Mac), NETUS-Eyes (iOS, Android)
Storage	ONVIF	ONVIF Profile S
	Primary / External	1 HDD
General	Size	340 x 60 x 300 mm
	Weight(w/o HDD)	3 Kg
	Temp / Humidity	5 ~ 40 °C / 10% ~ 80%
	PoE	Not Supported
	Power Supply	12V / 3.3A
	Power consumption	40W