


SWDNH-008F12AS



Dimensions



Product Summary

- Realtime with 1280x1440(240/200 fps)
- Half Realtime (120/100 fps)
- D1(NTSC/PAL), 960H(NTSC/PAL), 720p25/30, 720p50/60, 1080p25/30, 1440p15/25/30
- ONVIF or Vendor generic
- 300fps@4K2K + 300fps@D1/VGA
- 4 Line-in /1 Line-out & Audio on HDMI
- USB Device (HDD, Thumb Drive), NAS & Remote via Network
- Raw data format, Support with the Embedded Player
- One RS485 ports, PTZ using UCC
- Various resolution Size/Quality/FPS,
- Dual Streaming

Major Specifications

Model Name		SWDNH-008F12AS
Live Display (NTSC/PAL)	~1080p	Realtime (240/200 fps)
	1440p RT(1)	Realtime with 1280x1440 (240/200 fps)
	1440p NRT(2)	Half Realtime (120/100 fps)
Recording & Playback	D1, 960H,720p	240/200fps
	1080p	120/100fps
	1440p RT	120/100fps as 1080p
	1440p NRT	120/100fps as 1080p
Camera Input	Video Codec	H.264 / H.265
	No of Camera Resolution	8
IP Hybrid	No of IP Camera	D1(NTSC/PAL), 960H(NTSC/PAL), 720p25/30, 720p50/60, 1080p25/30, 1440p15/25/30
	Protocols	~10
	Live Display Performance	ONVIF or Vendor generic
Monitor Output	Record Performance	Realtime Display with the D1/VGA 2nd Stream of Camera I-Frame Only Display without substreams of IP camera for multiple ch view mode
	Main Monitor	300fps@4K2K + 300fps@D1/VGA
	SPOT Monitor	~4K30 for HDMI and 1080p60 for VGA
Audio In/Out		NTSC/PAL
Alarm In/Out		1,4, (6,7,8,9, (10,13,16, 20, 25)) for both live and playback
Storage		4 Line-in /1 Line-out & Audio on HDMI
Archive	SATA	8/2
	Backup Device	2
	Multiple channel AVI	USB Device (HDD, Thumb Drive), NAS & Remote via Network
USB Port		Raw data format, Support with the Embedded Player
Camera Control		Embedded AVI formatting
System Control		2 at Rear Panel
Network	Port	One RS485 ports, PTZ using UCC
	Protocols	USB Mouse, Front Keypad and IR Remote control are optionally possible.
	No of Client	10M/100M/1000M
Multi-Language		DHCP, DDNS, P2P, uPNP, HTTP, NTP, SNMP, SMTP, Push Notification(iOS/Android), ONVIF
Power		Max. 4
Operating Temperature		Support
Remote SW's		Adaptor (12V/3.3A, 2.5Ø)
Dimension (WxDxH, mm)		0~40 °C / 20~80% RH
Dedicated network streaming	Live	RMS / Web / MAC OSX / Android / iOS
	Playback	340x255x60
RAID(Mirroring)		Various resolution Size/Quality/FPS,
Search		Dual Streaming
P2P/DDNS/Push Notification/E-mail		Configurable Dual Recording
Event		Calendar/Time/Event/Panorama/Motion Area
Notification		ns.dynamicmv.com/P2P server/Relay Server/Push Server/Embedded E-mail Service
PoS I/F integration		Motion Detection, Alarm in, Video Loss, HDD S.M.A.R.T Status, HDD Error, Recording Status, POS
USER Privilege Set up		E-mail with snapshot, Buzzer, Pop-up, Symbol, Push Notification
Password Security		Extendable up to 8 PoS Interface
Recording Time Limit		Live/Search & Copy/Network/PTZ/Camera
Health Checking & Report		Periodically Password Refresh for all users
Easy Network Setup		12Hour, 1/2/3/4/5/6Day, 1/2/3Week, 1/2Month
		Periodical E-mail Report for HDD & Recording Status with various system info.
		P2P Service based Network Setup Wizard

(1) RT stands for 'Realtime Mode' at Camera Side
 (2) NRT stands for 'Non-Realtime Mode' at Camera Side